

In accordance with NBR 14725-4 / 2010

## **MATERIAL SAFETY DATA SHEET**

Nr. Review: 01 Emission/Review date: Last review date: Code: FISPQ-SGQ-42 02/10/2019

#### 1 - IDENTIFICATION OF THE SUBSTANCE AND THE COMPANY

## 1.1 Product Identifier Trade Name: Strike

### 1.2 Application of the product

It is a high-performance fabric protector developed for automotive and domestic upholstery.

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: EVC Industrial Ltda Elaboration: Paulo Henrique Sampaio Nobre

CRQ (Regional Chemistry Council): 10400261- 10th region

Address: Rua Luiz Francisco Xavier, 520, Paupina - Cep-60872-508

Company's telephone number: (085) 3274-2896 Emergency telephone number: 0800.014.1149

#### 2 - HAZARDS IDENTIFICATION

#### 2.1 Product Hazards:

**Adverse human health hazards:** The product may cause irritation to the eyes, respiratory tract and skin. Prolongated contact ought to be avoided to prevent health damage

**Environmental hazards:** Dispersion in the environment can contaminate the area. Avoid entering watercourses. Dangerous for aquatic organisms and may cause death.

**Specific hazards:** The product is classified as flammable.

**Main Symptoms:** In case of eye contact, pain, redness, blurred vision, a burning sensation may occur. In the case of ingestion, the symptoms can be a burning sensation, abdominal pain, diarrhea, nausea and vomiting. In the case of inhalation of large quantities of the product, headaches, a feeling of weakness, dry throat, cough, drowsiness, dizziness and nausea may occur.

#### 2.2 Classification of Substance or Mixture

Acute Toxicity Classification: Category 2

### 2.3 Signal Words

Warning!



In accordance with NBR 14725-4 / 2010

### **MATERIAL SAFETY DATA SHEET**

Nr. Review: 01 Emission/Review date: Last review date: Code: FISPQ-SGQ-42 02/10/2019

#### 2.4 Hazard Pictogram

Not required

#### 2.5 Hazard statements

H226 - Flammable liquid and vapor

H320 - Causes eye irritation

#### 2.6 Precautionary statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/.../equipment.

P242 - Utilize apenas ferramentas antifaiscantes.

P243 – Take precautionary measures against static discharge.

P264 – Wash thoroughly after handling.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

### 3 - COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture

**Chemical Nature:** Mixture of hydrocarbon with silicones **Ingredients or impurities that may contribute to the hazard:** 

Chemical name	CAS No.	Concentration %	Classification*	Notes
Butyl glycol	111-76-2	10 to 20%	2 and 4	Corrosion / irritation to skin - Category 2 Serious eye damage/eye irritation - Category 2A Aspiration hazard - Category 2 Acute toxicity - Oral - Category 4 Acute toxicity - Dermal - Category 4 Acute toxicity - inhalation - Category 4
Aliphatic hydrocarbons	64742-47-8	25 to 35%	2	Aspiration Hazard

<sup>\*</sup>Classification system adopted: Standard ABNT-NBR 14725-Part 2: 2009. Adoption of the Globally Harmonized System for the Classification and Labeling of Chemicals, UN.



In accordance with NBR 14725-4 / 2010

### **MATERIAL SAFETY DATA SHEET**

Nr. Review: 01 Emission/Review date: Last review date: Code: FISPQ-SGQ-42 02/10/2019

### 4 - FIRST-AID MEASURES

- **4.1 First aid measures:** Take the victim to an airy place. Remove contaminated clothing. Wash affected body parts with plenty of water and soap. If the victim is unconscious and no longer breathes, practice artificial respiration or oxygenation. Forward to the nearest medical service taking this file.
- **4.2 After Inhalation:** Remove the person to an airy place. If they are not breathing, give artificial respiration. If breathing is difficult, consult a seek medical service immediately.
- **4.3 After skin contact:** Immediately wash the affected area with soap and running water for at least 15 minutes. Remove contaminated clothing. In case of effects/symptoms, consult a doctor. Wash contaminated clothing before reuse.
- **4.4 After eye contact:** Flush eyes with plenty of water for at least 15 minutes. Preferably use an eyewash. Seek medical assistance immediately, always carrying the product label and MSDS with the necessary information.
- **4.5 After ingestion:** Do not induce vomiting. Seek medical assistance immediately. It is possible that vomiting occurs spontaneously and should not be avoided; in this case, lay the patient on their side to prevent aspirating waste. **WARNING**: Never give anything orally to an unconscious person. **What actions should be avoided**: Do not apply mouth to mouth breathing if the patient has ingested the product. Use an intermediate manual resuscitation or ambulatory equipment to perform the procedure.
- **4.6 Protection for first aid providers:** Avoid skin and inhalation contact with the product during the process.
- **4.7 Notes to doctor:** Treatment is symptomatic and supportive. In the case of ingestion, gastric emptying procedures such as gastric lavage should not be performed. In case of eye contact, wash with saline followed by occlusion and referral for ophthalmological evaluation.

### 5 - FIREFIGHTING MEASURES

- **5.1 Suitable extinguishing media**: Foam, CO<sub>2</sub>, chemical powder.
- **5.2 Unsuitable extinguishing media:** Jet of water directly onto the burning product, for it can spread violently and increase the intensity of the fire.
- **5.3 Special Procedures:** Evacuate the area and fight the fire from a safe distance. Use dikes to contain the water used in combat. Position yourself with your back to the wind. Use water in mist form to cool equipment exposed in the vicinity of the fire.
- **5.4 Hazardous Decomposition Products:** Exposed to fire, product decomposition releases carbon monoxide, carbon dioxide and smoke, making the environment asphyxiating. Use a self-contained respirator to approach.
- **5.5 Special protective equipment for firefighting:** Self-contained breathing apparatus and appropriate clothing for firefighting.
- **5.6 Firefighting measures:** Respiratory equipment and protective clothing must be used in firefighting involving chemicals. Boiling points are reported in the respective product safety data



In accordance with NBR 14725-4 / 2010

## **MATERIAL SAFETY DATA SHEET**

Nr. Review: 01 Emission/Review date: Last review date: Code: FISPQ-SGQ-42 02/10/2019

sheets. It determines the need to evacuate or isolate the area, according to your local emergency plan. Use a water jet to keep the container fresh.

### 6 - ACCIDENTAL RELEASE MEASURES

- **6.1 Personal precautions:** Wear waterproof coveralls, protection goggles, rubber boots and PVC or nitrile rubber gloves. Respiratory protection must be carried out depending on the concentrations present in the environment or the extent of the spill/leak; for that, one must opt for full-face or semi-face masks with a replaceable filter or air adduction respirators (e.g., self-contained masks).
- **6.2 Removal of ignition sources**: Interrupt electrical power and turn off sources that generate sparks. Remove all local material that could cause a fire. (e.g., diesel oil). Dust control: not applicable because it is a liquid.
- **6.3:** Prevention of inhalation and contact with skin, mucous membranes and eyes: Wear clothing and accessories as described above, in Item 6.1 Personal Precautions
- **6.4: Environmental precautions:** Avoid contamination of watercourses by preventing the entrance of rainwater galleries (wolf mouth). Prevent spilled product residues from reaching water collections by building dikes with earth, sand or other absorbent material.
- **6.5 Methods and material for containment and cleaning up:** Contain and collect spill with non-combustible absorbent materials (e.g., sand, earth, vermiculite, diatomaceous earth). Place the waste in a container for further treatment in accordance with local regulations. Clean preferably with a detergent; avoid the use of solvents.
- **6.6 Prevention of secondary hazards:** Avoid the product that contains streams, lakes, water sources, wells, rain photos and effluents.

### 7 - HANDLING AND STORAGE

- **7.1 Fire and explosion prevention:** Do not store with incompatible materials.
- **7.2 Prevention of worker exposure:** Wear PPE (boots, gloves, apron and protection goggles) when handling the product. Do not eat, drink or smoke when handling the product. When opening the packaging, do so to avoid leakage. Do not use damaged or defective personal protective and application equipment. Do not handle and/or load damaged packaging.
- **7.3 Precautions for safe handling:** Use PPE as described in Item 8. Do not mix with chemical products, mainly with chlorine (e.g., bleach) and ammonia-based products.
- **7.4 Guidelines for safe handling:** Use PPE as described in Item 8. Handle the product with the appropriate local exhaust or in a well-ventilated area; if in open environments, handle it with the wind. Apply only the doses recommended by the product registrant (see label).

#### 7.5 Storage

**Adequate storage conditions:** Keep the product and, if necessary, leftovers in their original used packaging closed.



In accordance with NBR 14725-4 / 2010

## **MATERIAL SAFETY DATA SHEET**

Nr. Review: 01 Emission/Review date: Last review date: Code: FISPQ-SGQ-42 02/10/2019

### 7.6 Storage conditions

**Adequate:** Keep the container closed adequately at room temperature and protected from light. Store it in a duly identified location. Lock the place to prevent unauthorized people from accessing screens.

To avoid: Places with heat sources.

**Incompatible products and materials:** Oxidizing agents. Do not store together with food, drinks, including those intended for animals.

### 7.7 Safe packaging materials

**Recommended:** Product already packed in appropriate packaging.

### 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

**8.1 Engineering control measures:** Use fans, air circulators, exhaust fans; provide adequate ventilation to the workplace.

### **8.2 Occupational Exposure Limits:**

Component	No. CAS	Agency	Limit	Notes
Hidrocarbonetos alifáticos	64742-47-8	CMRG	TWA: 165 ppm	ND
Butyl glycol	111-76-2	NR-15 - ACGIH	TWA: 39 ppm	ND

NR-15 (Regulatory standard no. 15)

ACGIH - American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

### 8.3 Physical and chemical properties:

**Hand protection**: Gloves during the handling process to avoid direct and prolonged contact with the product.

**Eye protection:** In operations where splashes may occur, the use of safety glasses is recommended.

**Hygiene measures:** General control methods used in industrial hygiene should minimize exposure to the product. Do not eat, drink or smoke when handling chemicals—separate work clothes from ordinary clothes.

**Respiratory protection:** In the process of spraying the product, it is recommended to use a respiratory protector.



In accordance with NBR 14725-4 / 2010

### **MATERIAL SAFETY DATA SHEET**

Nr. Review: 01 Emission/Review date: Last review date: Code: FISPQ-SGQ-42 02/10/2019

### 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Aspect: Net9.2 Color: Orange

9.3 Odor: Characteristic

9.4 pH: ND

9.5 Specific temperatures or temperature ranges in which physical state changes occur: ND

9.6 Boiling point: ND9.7 Melting point: ND9.8 Flashpoint: ND

**9.9 Lower explosive limit:** ND **9.10 Upper explosive limit:** ND

9.11 Specific gravity: ND9.12 Steam pressure: ND

9.13 Auto-ignition temperature: ND
9.14 Density 20 ° C: 0.84 to 0.86 g/cm<sup>3</sup>
9.15 Solubility in water: Insoluble
9.16 Auto flammability: ND
9.17 Coefficient participation: ND

9.18 Asset content: ND

### 10 - STABILITY AND REACTIVITY

### 10.1 Chemical stability

The product is stable at room temperature, under normal conditions of use and storage.

### 10.2 Conditions to avoid

Temperatures above 50 °C, exposure to direct sunlight.

### 10.3 Hazardous decomposition products:

Fire can release toxic gases and vapors that are harmful to human health.

### 10.4 Reactivity

Flames and sparks

### 10.5 Possibility of hazardous reactions

Flames and sparks

### 10.6 Incompatible materials or substances

Water



In accordance with NBR 14725-4 / 2010

### **MATERIAL SAFETY DATA SHEET**

Nr. Review: 01 Emission/Review date: Last review date: Code: FISPQ-SGQ-42 02/10/2019

### 11 - TOXICOLOGICAL INFORMATION

**11.1 Local effects:** The product may cause local irritation, depending on the form of contact and other symptoms, as described in Item 2. The toxicological information values set out below may not reflect the toxicity value of the product because the ingredients may be below concentration, may not be available for exposure or may not be relevant to the material as a whole.

### 11.2 Acute toxicity:

Name	Route	Specie	Value
Product	Dermis	-	Estimated value LD50 > 5000 mg/Kg
Product	Ingestion	-	Estimated value LD 50 > 5000 mg/Kg
Butil glicol	Ingestion	Rat	LD50 = 1726 mg/Kg
Butil glicol	Inhalation	Rat	LC50 = 2,2 mg/L
Aliphatic hydrocarbons	Dermis	Rabbit	LD50 > 3.160 mg/kg
Aliphatic hydrocarbons	Inhalation	Rat	LC50 > 3.0 mg/kg
Aliphatic hydrocarbons	Ingestions	Rat	LD50 > 5.000 mg/kg

LD - Lethal dose

- **11.3 Skin corrosion/irritation:** Based on the available information, this product does not have a classification for this criterion.
- **11.4 Serious eye damage/irritation:** Based on the available information, this product does not have a classification for this criterion.
- **11.5 Skin sensitization:** Based on the available information, this product does not have a classification for this criterion.
- **11.6 Mutagenicity:** Based on the available information, this product does not have a classification for this criterion.
- **11.7 Carcinogenicity:** Based on the available information, this product does not have a classification for this criterion.
- **11.8 Chronic Toxicity:** Based on the available information, this product does not have a classification for this criterion.

LC -Lethal concentration



In accordance with NBR 14725-4 / 2010

### **MATERIAL SAFETY DATA SHEET**

Nr. Review: 01 Emission/Review date: Last review date: Code: FISPQ-SGQ-42 02/10/2019

### 12 - ECOLOGICAL INFORMATION

### 12.1 Environmental, behavioral effects and product impacts

Mobility: ND

**Environmental behavior:** Effects are not expected in consequence of proper use of the product. However, its improper use and contact with soil or aquatic environment can cause imbalance

and damage.

Degradability: ND

Bioaccumulation: ND

Ecotoxicity: ND

### 13 - TREATMENT AND DISPOSAL CONSIDERATION

#### 13.1 Waste treatment methods:

**Product:** Deactivate the product through incineration in ovens intended for this type of operation, equipped with chambers for washing effluent gases and approved by the competent body.

**Product remnants:** Do not dispose of product leftovers improperly after use. Depending on the available quantity, store appropriately for a new application. Keep any leftovers with expired validity in their original containers adequately closed.

**Used package:** Empty packaging must be stored in a safe place for later return to the commercial establishment where it was acquired within one year. Do not burn or bury packaging. Observe specific State and Municipal Legislation. Consult the State or Municipal Environment Agency.

### 14 - TRANSPORT INFORMATION

14.1 UN-Number	
ADR, IMDG, IATA	Void
14.2 UN Proper Shipping Name	
ADR, IMDG, IATA	Void
14.3 Transport Hazard Class(es)	
ADR, IMDG, IATA	Void
Class	
14.4 Packing Group	
ADR, IMDG, IATA	Void
14.5 Environmental Hazards	
	Not applicable
14.6 Special Precautions for user	Not applicable
14.7 Transport in bulk according to Annex II of	Not applicable



In accordance with NBR 14725-4 / 2010

### **MATERIAL SAFETY DATA SHEET**

Marpol and the IBC Code

### 15 - REGULATORY INFORMATION

- **1.5 National and international land/waterway/air regulations:** Non-hazardous product according to transport regulation criteria.
- **15.2 International regulations:** Contact EVC Industrial for further information

### 16 - OTHER INFORMATION

The information and recommendations contained in this MSDS were obtained from



In accordance with NBR 14725-4 / 2010

### MATERIAL SAFETY DATA SHEET

Nr. Review: 01 Emission/Review date: Last review date: Code: FISPQ-SGQ-42 02/10/2019

reputable sources and based on previous experiences, refer to this specific product and are valid when used according to the label's guidelines. This document was approved electronically.

#### ABBREVIATIONS AND ACRONYMS

**NA**: Not applicable **ND**: Not Determined

**OSHA**: Occupational Safety and Health Administration.

LD50: Lethal dose, 50 percent

**LC50**: Lethal concentration, 50 percent **CAS**: Chemical Abstracts Service.

**TLV-TWA**: Threshold Limit Value – Time-Weighted Average **TLV-STEL**: Threshold Limit Value – Short-term exposure

**ACGIH**: American Conference of Governmental Industrial Hygienists is an organization open to all practitioners in industrial hygiene, occupational health, environmental health, or safety.

PEL: Permissible Exposure Limit

**OSHA**: Occupational Safety and Health Administration.

**GGVE/GGVS**: Gefahrgutverordnung Eisenbahn Bzw Strasse – decree on the transport of hazardous materials by land (railroad and highway).

**GGV-See**: Gefahrgutverdnungg-See – decree on the transport of hazardous materials by sea. **IMDG**: International Maritime Dangerous Goods – international code for the transport of hazardous materials by sea.

**CAO**: Cargo Aircraft Only – cargo authorized for transportation by cargo plane.

**PAX**: Passenger Aircraft – amount allowed for transportation on a commercial airplane.

**AEL**: is the acceptable exposure limit. In places where the occupational exposure limits imposed by government agencies are lower than the AEL, these limits should be preferred.