

MATERIAL SAFETY DATA SHEET

Nr. Review: 01	Emission/Review date: 17/03/2020	Last review date: 22/05/2019	Code: FISPQ-SGQ-30
----------------	-------------------------------------	---------------------------------	--------------------

1 – IDENTIFICATION OF THE SUBSTANCE AND THE COMPANY

1.1 Product Identifier

Trade Name: Impact

1.2 Application of the product

It is a universal cleaner used for difficult cleaning on different surfaces.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: EVC Industrial Ltda

Elaboration: Paulo Henrique Sampaio Nobre

CRQ (Regional Chemistry Council): 10400261- 10th region

Address: Rua Luiz Francisco Xavier, 520, Paupina - Cep-60872-508

Company's telephone number: (085) 3274-2896

Emergency telephone number: 0800.014.1149

2 – HAZARDS IDENTIFICATION

2.1 Product Hazards:

Adverse human health hazards: Contact with eyes may irritate.

Environmental hazards: May contaminate soil and rivers.

Specific hazards: The product is not classified as a dangerous product.

Chemical Hazard: N/A

2.2 Classification of Substance or Mixture

Acute Toxicity Classification: Category 5

2.3 Signal Words

Warning!

2.4 Hazard Pictogram

Not required

2.5 Hazard statements

H303 - May be harmful if swallowed

H320 - Causes eye irritation

2.6 Precautionary statements

P312 - Call a Poison Center/Doctor if you feel unwell

MATERIAL SAFETY DATA SHEET

Nr. Review: 01	Emission/Review date: 17/03/2020	Last review date: 22/05/2019	Code: FISPQ-SGQ-30
----------------	-------------------------------------	---------------------------------	--------------------

3 - COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture

Chemical Nature: General cleaner

Ingredients or impurities that may contribute to the hazard:

Chemical name	CAS No.	Concentration %	Classification*	Notes
Butyl glycol	111-76-2	5 to 10%	2 and 4	Corrosion/irritation to skin - Category 2 Serious eye damage/eye irritation - Category 2A Aspiration hazard - Category 2 Acute toxicity - Oral - Category 4 Acute toxicity - Dermal - Category 4 Acute toxicity - inhalation - Category 4
Metasilicate	6834-92-0	4 to 8%	ND	ND

*Classification system adopted: Standard ABNT-NBR 14725-Part 2: 2009. Adoption of the Globally Harmonized System for the Classification and Labeling of Chemicals, UN.

4 - FIRST-AID MEASURES

4.1 After skin contact: Remove contaminated clothes and shoes, wash the affected parts under running water.

4.2 After eye contact: Remove contact lenses. Wash with under running water. If irritation persists, consult a physician taking the product packaging or label.

4.3 After ingestion: Do not induce vomiting and immediately consult the Poison Center or the doctor taking the product label. Emergency phone number.

4.4 Recommendations for the Doctor: Evaluate the composition described on the label.

5 – FIREFIGHTING MEASURES

5.1 Suitable extinguishing media: Non-flammable product. If a fire starts with other materials, use fire-extinguishing CO2, chemical powder and water extinguishing agent.

5.2 For safety reasons, unsuitable extinguishing agents: Do not use water extinguishing agent, when there is energized sources on site.

5.3 Specific hazards: There is no specific hazard due to its restriction containing more than 70% water.

5.4 Special firefighting methods: The product does not present a risk for special fire methods. Non-flammable product.

MATERIAL SAFETY DATA SHEET

Nr. Review: 01	Emission/Review date: 17/03/2020	Last review date: 22/05/2019	Code: FISPQ-SGQ-30
----------------	-------------------------------------	---------------------------------	--------------------

5.5 Special equipment for the protection of firefighters: Due to the characteristics of the product, it is not necessary to use special equipment other than those commonly used.

6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions: Remove unnecessary people from the area. Use PPE. If possible, stop the spill or leak source.

6.2 Environmental precautions: Avoid contamination of watercourses by preventing the entrance of rainwater galleries (wolf mouth). Prevent spilled product residues from reaching water collections by absorbing the product with absorbent material (e.g., sawdust, sand or clay). Contact your local security authorities.

6.3 Methods and material for containment and cleaning up: Contain and collect spill. Place the waste in a container for disposal according to local regulations. Clean preferably with water, avoiding the use of solvents. For large spills, contain the liquid in dikes and pump it into suitable containers.

7 - HANDLING AND STORAGE

7.1 Technical measures: Keep people, especially children, and pets away from the workplace.

7.2 Prevention of worker exposure: Use PPE as described in item 8.

7.3 Guidelines for safe handling: Do not eat, drink, or smoke in the workplace. Wash thoroughly after handling. Do not ingest. Avoid inhalation, aspiration, contact with eyes, and skin. Keep out of the reach of children and pets. Do not reuse the packaging for other purposes. Keep the product in its original package. Do not mix with other products.

7.4 Storage

Adequate storage conditions: Keep the container closed adequately at room temperature and protected from light.

To avoid: Humid places with high temperatures.

Incompatible products and materials: Oxidizing agents. Do not store together with food, drinks, including those intended for animals.

8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 Engineering control measures: Use fans, air circulators, exhaust fans; provide adequate ventilation to the workplace.

8.2 Occupational Exposure Limits:

Component	CAS No.	Agency	Limit	Notes
Butyl glycol	111-76-2	NR-15 - ACGIH	TWA: 39 ppm	ND
Metasilicate	67-63-0	NR-15 - ACGIH	TWA: 2 mg/m ³	ND

NR-15 (Regulatory Standard No. 15)

ACGIH - American Conference of Governmental Industrial Hygienist

TWA: Time-Weighted-Average

MATERIAL SAFETY DATA SHEET

Nr. Review: 01	Emission/Review date: 17/03/2020	Last review date: 22/05/2019	Code: FISPQ-SGQ-30
----------------	-------------------------------------	---------------------------------	--------------------

8.3 Physical and chemical properties:

Hands: Gloves in the handling process to avoid direct and prolonged contact with the product.

Eyes: In operations where projections or splashes may occur, the use of protective goggles is recommended.

9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Aspect: Net

9.2 Color: Orange

9.3 Odor: Characteristic

9.4 Specific temperatures or temperature ranges in which physical state changes occur: ND

9.5 Boiling point: 110°C

9.6 Melting point: ND

9.7 Flashpoint: ND

9.8 Lower explosive limit: ND

9.9 Upper explosive limit: ND

9.10 Specific gravity: ND

9.11 Steam pressure: ND

9.12 Auto-ignition temperature: ND

9.13 Density: 0.99 to 1.02 g/cm³

9.14 Solubility in water: Soluble

9.15 Auto-ignition: ND

9.16 Coefficient participation: ND

9.17 Asset content: ND

10 - STABILITY AND REACTIVITY

10.1 Chemical stability

The product is stable at room temperature, under normal conditions of use and storage.

10.2 Conditions to avoid

Temperatures above 50 °C, exposure to direct sunlight.

10.3 Hazardous decomposition products:

Fire can release toxic gases and vapors that are harmful to human health.

10.4 Reactivity

Atmospheric air

10.5 Possibility of hazardous reactions

None

10.6 Incompatible materials or substances

None

MATERIAL SAFETY DATA SHEET

Nr. Review: 01	Emission/Review date: 17/03/2020	Last review date: 22/05/2019	Code: FISPQ-SGQ-30
----------------	-------------------------------------	---------------------------------	--------------------

11 - TOXICOLOGICAL INFORMATION

11.1 Local effects: The product may cause local irritation, depending on the form of contact and other symptoms, as described in Item 2. The toxicological information values set out below may not reflect the toxicity value of the product because the ingredients may be below concentration, may not be available for exposure or may not be relevant to the material as a whole.

11.2 Acute toxicity:

Nome	Rota	Espécie	Valor
Product	Dermis	-	Estimated value LD50 > 5000 mg/Kg
Product	Ingestion	-	Estimated value LD50 > 5000 mg/Kg
Butyl glycol	Ingestion	Rat	LD50 = 1726 mg/Kg
Butyl glycol	Inhalation	Rat	LC50 = 2,2 mg/L
Metasilicate	Ingestion	Rat	LD50 = 847 mg/Kg
Metasilicate	Dermis	Rat	LD50 = 1350 mg/Kg

LD – Lethal dose

LC – Lethal dose

11.3 Skin corrosion/irritation: Based on the available information, this product does not have a classification for this criterion.

11.4 Serious eye damage/irritation: Based on the available information, this product does not have a classification for this criterion.

11.5 Skin sensitization: Based on the available information, this product does not have a classification for this criterion.

11.6 Mutagenicity: Based on the available information, this product does not have a classification for this criterion.

11.7 Carcinogenicity: Based on the available information, this product does not have a classification for this criterion.

11.8 Chronic Toxicity: Based on the available information, this product does not have a classification for this criterion.

12 – ECOLOGICAL INFORMATION

12.1 Environmental, behavioral effects and product impacts

Mobility: ND

MATERIAL SAFETY DATA SHEET

Nr. Review: 01	Emission/Review date: 17/03/2020	Last review date: 22/05/2019	Code: FISPQ-SGQ-30
----------------	-------------------------------------	---------------------------------	--------------------

Environmental behavior: Effects are not expected in consequence of proper use of the product. However, its improper use and contact with soil or aquatic environment can cause imbalance and damage.

Degradability: ND

Bioaccumulation: ND

Ecotoxicity: ND

13 – TREATMENT AND DISPOSAL CONSIDERATION

13.1 Waste treatment methods:

Product: The product must be collected in containers for final determination under current legislation. The improper destination of empty packaging and product remains in the environment causes contamination of the soil, water and air, harming fauna, flora and people's health.

Used package: This package can be washed and recycled. Throw the empty packaging in the trash.

14 - TRANSPORT INFORMATION

National and international land/waterway/air regulations: Non-hazardous product according to transport regulation criteria.

15 – REGULATORY INFORMATION

15.1 National regulations: SANITATING PRODUCT NOTIFIED AT ANVISA, No. 25351.599763/2019-64, according to current legislation.

15.2 International regulations: Contact EVC Industrial for further information

16 - OTHER INFORMATION

The information and recommendations contained in this MSDS were obtained from reputable sources and based on previous experiences, refer to this specific product and are valid when used according to the label's guidelines. This document was approved electronically.

MATERIAL SAFETY DATA SHEET

Nr. Review: 01	Emission/Review date: 17/03/2020	Last review date: 22/05/2019	Code: FISPQ-SGQ-30
----------------	-------------------------------------	---------------------------------	--------------------

ABBREVIATIONS AND ACRONYMS

NA: Not applicable

ND: Not Determined

OSHA: Occupational Safety and Health Administration.

LD50: Lethal dose, 50 percent

LC50: Lethal concentration, 50 percent

CAS: Chemical Abstracts Service.

TLV-TWA: Threshold Limit Value – Time-Weighted Average

TLV-STEL: Threshold Limit Value – Short-term exposure

ACGIH: American Conference of Governmental Industrial Hygienists is an organization open to all practitioners in industrial hygiene, occupational health, environmental health, or safety.

PEL: Permissible Exposure Limit

OSHA: Occupational Safety and Health Administration.

GGVE/GGVS: Gefahrgutverordnung Eisenbahn Bzw Strasse – decree on the transport of hazardous materials by land (railroad and highway).

GGV-See: Gefahrgutverdnungg-See – decree on the transport of hazardous materials by sea.

IMDG: International Maritime Dangerous Goods – international code for the transport of hazardous materials by sea.

CAO: Cargo Aircraft Only – cargo authorized for transportation by cargo plane.

PAX: Passenger Aircraft – amount allowed for transportation on a commercial airplane.

AEL: is the acceptable exposure limit. In places where the occupational exposure limits imposed by government agencies are lower than the AEL, these limits should be preferred.